



CX10 - 10" Countertop / Under Cabinet Touchpanel



From the executive boardroom to the gourmet kitchen, the CX10 delivers intuitive control and a high-end entertainment experience in a sleek touchpanel design. The CX10's 10-inch, high-resolution LCD screen offers ample space to create the ultimate custom user interface. With this level of personalization, any user can confidently manipulate the environment and entertainment. The versatile CX10 also doubles as a display for watching an HD movie or a television show via the integrated HDBaseT video input and stereo speakers. Easy to mount on a countertop or beneath a cabinet, the touchpanel display has a tilt range from 10 degrees to 90 degrees for the best viewing angle possible. Additional user-friendly features include video intercom support, composite video viewing and a proximity sensor.

Installation Options



Key Features

- 10.1" widescreen LCD with 1280x800 (WXGA) resolution and integrated capacitive touchscreen.
- Displays HD video via the integrated HDBaseT video input (1080p/1080i/720p/480p resolution video support).
- View analog video sources such as security cameras via the composite video input.
- Stereo audio input and speakers.
- Integrated 10/100 Base-T (with PoE+) and 802.11b/g/n wireless Ethernet.
- Video intercom capability via the built-in camera, microphone, and speakers.
- Proximity sensor automatically wakes the unit as a user approaches.
- Ambient light sensor automatically adjusts the backlighting.
- Built-in high output IR port for direct control of devices through an IR connecting block.
- Powered by power supply (included), an RTI CB8 connecting block or PoE+ (Power over Ethernet Plus).
- Countertop or under cabinet (inverted) mounting option and adjustable tilt display (10°-90°).

Included in the Box

CX10, power supply (12V, 2A), rotatable RTI logo (1), mounting bracket (1), ferrite clamp


Specifications

Power +12VDC to +16VDC, 2A max
 Power Management Adjustable backlight
 brightness/proximity sensor
 Touchscreen Display High-brightness color TFT LCD
 WXGA (1280x800 pixels) with 65K colors
 Integrated high-resolution projected capacitive touchscreen
 Display Size 10.1in (256mm) diagonal
 Display Backlight LED Backlit, 212nit
 Infrared Output Through control port, 200mA output
 Drives up to 1000ft (300m) of wire
 Ethernet Port RJ-45, 10/100 Base-T
 with Power-over-Ethernet Plus
 Wireless Ethernet 802.11b/g/n
 Camera Color CMOS VGA (640x480)
 Microphone Silicon MEMS
 Speakers Two (2), Stereo 2 Watt, 8 Ohm, 83dB
 Communications USB programming port
 Video Input RJ-45, HDBaseT
 RCA Connector, Composite Analog Video
 NTSC/PAL/SECAM
 System Memory 512MBytes Flash (non-volatile) memory
 Device Capability Total number of devices
 is limited only by memory
 Macro Capability Unlimited steps in a single macro
 Total number of macros is limited only
 by memory. Macro capability on every button

Operating Temperature +32°F to +122°F (0°C to +50°C)
 Operating Humidity 5% to 95% Non-condensing
 Enclosure High-impact molded ABS plastic
 Mounting Tabletop, or screws through
 mounting bracket (Included)
 Dimensions (LxWxH) 8.97 in x 9.90 in x 8.24 in
 227.8 mm x 251.64 mm x 209.49 mm
 Weight 3.84lbs (1744g)
 Warranty Three Years (Parts & Labor)

All Specifications subject to change without notice.

Features



Do more with Integration Designer 11

Integration Designer 11 elevates the experience for all RTI systems, from residential to commercial. Its stunning new template - complete with custom slider support, one-click background swapping and more - makes it faster than ever to deliver a beautiful finish to every installation. Drivers are directly accessible from within the software, with notifications to keep you always up to date. The integrated system manager lets you track rooms, rooms status, and source status to save time on every installation. All this and more in [Integration Designer 11](#).

